

Benefits

1. unique dispersion properties ensure excellent cleaning of all engine components
2. high stability of lubricating film and reliable wear protection
3. optimal fuel combustion

Product Description

BIZOL Allround 5W-20 is a modern HC-synthetic engine oil. The carefully selected combination of base oils and special additive components results in an engine oil with good fuel saving properties. Gasoline vehicles benefit from this modern engine oil technology. It prevents deposit formation on the piston as well as piston rings. A sophisticated selection of additives prevents sludge formation caused by oxidation. **BIZOL Allround 5W-20** provides a fast lubrication of the engine and as a result significantly reduces wear during cold starts. It minimizes the risk of LSPI.



Base Oil

HC-Synthetic

Specifications/Approvals & Recommendations

API SP/SN Plus | ILSAC GF-6A

GM DEXOS 1 Gen. 2/6094 M | Ford WSS-M2C-960-A1 |

Chrysler MS-6395

Available Packages

1 L
Art. 84420

5 L
Art. 84421

Technical Data

Name	Value	Method
Viscosity class SAE	5W-20	SAE J 300
Viscosity at 100 °C	45,7 mm ² /s	ASTM D 7042
Viscosity at 40 °C	8,6 mm ² /s	ASTM D 7042
Viscosity index	168	ASTM D 2270

Technical Data

Name	Value	Method
Density at 15 °C	850 kg/m ³	DIN EN ISO 12 185
Pour Point	-36 °C	ISO 3016
ASTM colour number	L2,0	ASTM D1500
Flash Point (Cleveland)	225 °C	ISO 2592
Total base number (TBN)	6,0 mg KOH/g	ASTM D 2896
Sulfate ashes	0,90 %	DIN 51 575
High Shear / High Temperature Viscosity	2,6 mPa,s	ASTM D 5481